



BEHR® FAST DRYING WATER-BASED POLYURETHANE

- Durable Crystal Clear Protective Finish
- Recoat in 1 Hour
- Resists Stains and Scratches
- Self-Leveling, Smooth Finish
- Less Odor Than Oil-Based Finishes
- Dries to Touch in 1 Hour

No. B8100 Series

Available in
Satin, Semi-Gloss,
Gloss, and Matte



Prep Before Use



2 Coats Required
3 Coats if Desired



Spread Rate:
125 Sq. Ft. / Qt.



Clean-Up:
Soap & Water

READY TO USE. PROTECT FROM FREEZING.

WHERE TO USE: Properly prepared interior bare or stained wood surfaces such as furniture, moldings, cabinets, trim, doors and residential hardwood floors

CAUTION: Top coated surfaces may be slippery when wet.

SURFACE PREPARATION†

(The following steps are recommended for best results.)

- For refinishing, remove all wax or cleaner build-up with a wax stripper or degreaser prior to sanding.
- Sand all surfaces in the direction of the wood grain to desired smoothness.
- DO NOT USE steel wool.
- Remove all dust from sanded surfaces and clean with tack cloth.

APPLICATION

- Do not shake or thin.
- Do not apply in direct sunlight or in temperatures below 55°F (10°C) or above 90°F (32°C).
- Stir thoroughly prior to and during use.
- If wood stain color is desired, apply BEHR® Wood Stain. Follow all label instructions.
- Using a high quality nylon/polyester bristle brush, dip approximately an inch into the can, gently tapping it against the inside to remove any excess.
- Apply a thin, even coat following the direction of the grain making sure to maintain a wet edge.
- To minimize the brush marks and bubbles after application, tip off the surface by holding the brush at a 45 degree angle and lightly run the bristles over the entire length of the wood.
- Floor Application: use a synthetic pad applicator or bristle brush and maintain a wet edge to avoid lap marks. For maximum durability, 3 coats are required.
- Do not puddle, over-brush or overlap finishes. Sand lightly between coats with fine sand paper. Remove all dust prior to applying additional coats.

DRY TIME

- Dries to the touch in 1 hour. Sand or Recoat: 1 hour. After final coat, allow 12 - 24 hours before light use. Fully cured: 3 days after final coat.

DISPOSAL

- For disposal of empty containers and unused product, contact your household refuse collection service.

LIMITED WARRANTY

- Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

†**WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠ **WARNING** Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.

PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.



©2021 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 9/21